



SEALFLEX



ELASTOMERIC ROOF COATING

WATER BASED / FLEXIBLE AND ELASTIC / WATERPROOF

ESTHETIC AND OPAQUE
APPLIES WITH ROLLER OR PAINTBRUSH
EXTENDS ROOF LIFE

WATER BASED / FLEXIBLE AND ELASTIC / WATERPROOF
PROTECTS AND SEALS / CONTAINS ANTI-RUST AGENT / FOR:

CARAVAN & RECREATIVE
VEHICLE ROOFS



AVAILABLE IN 5 COLORS



Black



Grey



White



Green



Brown


STEEL, WOOD AND
CONCRETE ROOFS



ASPHALT SHINGLES
ROOFS AND OTHERS



1. Repair broken or edge lifted shingles, replace missing parts



2. Clean surface



3. Apply



- Avoid application under a full sun or over too hot surfaces
- Shake well before use, do not dilute
- Test on a small area to determine suitability of product
- For application and curing of SEALFLEX, it is necessary to have a temperature higher than 10°C until completely dry
- It is recommended to apply 2 coats. Let dry between coats. Apply with a paintbrush, a roller or an industrial sprayer
- Clean tools with Water while product is still fresh

CAUTION: Do not apply over roofs covered with tar or gravel. Do not use over a deteriorated roof that needs major repairs. Do not begin outside work if temperature is unsure for the next 48 hours. Store at temperatures between 10°C and 30°C. Make sure that work is done in a safe manner.

1 L of SEALFLEX covers up to 3,2 m² (34 ft²). Coverage rate may vary according to application method, applicator's skills, porosity and surface conditions. Foresee a supplementary quantity if made by a non-professional.

Read warning part and complete application method on label or on technical data sheet before using this product.



CONDOR CHIMIQUES INC.
ST-CYRILLE, QUÉBEC J1Z 1B3
www.condorchimiques.com

